

## **2022 – Limited Late Model Rules**

### **AREAS HIGHLIGHTED IN RED ARE CHANGES FOR THIS SEASON**

*Variations from any specification or rule must be approved by the speedway tech officials.*

#### **Minimum Age Requirements:**

All drivers must meet minimum age requirements to compete at Selinsgrove Speedway. All drivers under the age of 18 must have a parent/guardian consent form on file in the speedway office before competing. Competing/Driving at Selinsgrove Speedway for the purpose of age restriction is defined as anytime the race vehicles wheels are turning, regardless of whether the vehicle is under its own power or not. Birth Certificate or other proof of age may be required. Minimum age restrictions for competing/driving in the Limited Late Model division is 16 years of age.

**Exceptions** – Exceptions to Selinsgrove Speedway age limits will only be granted to drivers holding a license/membership in a sanctioning body (ie..United Racing Club, Empire Super Sprints, World of Outlaws, etc.), provided said driver meets the minimum age requirements for that sanctioning body. The exception is only granted for events that the sanctioning body where the driver holds a license/membership is sponsoring or co-promoting/sanctioning at Selinsgrove Speedway.

#### **Engines**

11 to 1 compression ratio maximum.

A maximum of 25.5 inches from the center of the ball joint to the front of the motor plate/engine bell housing flange will be permitted.

All engines must have crankcase openly vented. Mopar-Max.cu. in. 366 (.030 maximum over bore) Ford-Max. cu. in. 357 (.030 maximum over bore) Chevrolet-Max. cu. in. 355 (.030 maximum over bore)

Crate Engines - GM Crate Engines 88958602 AND 19318604 will be eligible to compete in sealed form with a 2- or 4-barrel carburetor.

#### **Ignitions**

Only a single distributor or magneto will be permitted. Coil pack and/or engines that have individual ignition systems, electronic or mechanical for each cylinder will not be permitted.

Aluminum intakes are permitted

Headers are permitted.

#### **Carburetors**

A maximum of four barrels of carburetion permitted. Only one carburetor per engine is permitted.

No super chargers, fuel injection or turbo chargers.

The carburetors, float bowls, booster, venturi area (casting ring may be removed), butterflies, throttle shaft and base plate may be altered.

The choke may be removed but all screw holes must be permanently sealed. The choke horn may be removed.

The idle holes may be drilled and the butterfly screw ends may be cut even with the shaft.

Carburetor jets may be changed.

Modifications or components to increase or restrict airflow to the carburetors (such as velocity stacks, heat deflector shields, internal modifications not listed above, etc.) are not permitted.

Carburetor Adapter: Only a one or two-piece aluminum or phenolic carburetor adapter may be installed between the intake manifold and carburetor. A one-piece gasket may be installed between the carburetor and adapter and between the intake manifold and adapter.

### **Cylinder Heads**

Any factory steel cast iron cylinder head, **Dart Iron Eagle 215cc, Mowtown 220cc**, World Products Sportsman II steel head with casting number must be #1037 or any bow-tie Vortex heads are permitted. The cylinder head must remain in unaltered "as cast" condition unless otherwise noted. No aluminum heads. Relocating rocker arm studs is not permitted. Ford engines may use the following cast iron cylinder heads: ProAction (part numbers 35301, 35302 or 35303); World Products Windsor Sr. (Casting #1-061); Dart Iron Eagle (casting numbers 13310010, 13410010, 13500020 or 13520020). N heads permitted.

All heads must have a minimum 60cc combustion chamber. The "cc" measurement of the intake runner of head must remain stock with the exception of matching port.

Matching ports in the intake port of head is permitted. The depth maximum for matching ports is 0.75". The valve seat area may be cleaned up using a maximum 80-degree grinding stone. Screw-in studs, stud girdles and guide plates are permitted.

Unless otherwise stated, any cylinder head with evidence of sanding, polishing, relieving, grinding, porting, angle milling, chemical treating, abrasive blasting to the original cast form, will be declared illegal and penalized. O-ringing the head gasket seal area is not permitted.

Combustion Chamber: The combustion chamber may be altered in but must still be 60 CC.

### **Camshafts**

Flat tappet cams only are permitted. No roller cams, no roller lifters, no radius lifters, no mushroom lifters permitted. Roller rockers are permitted.

All blocks and heads must be cast iron.

### **GM Crate Engine 88958602 Specifications**

Block part number: 10105123

Block type: cast iron with 4-bolt main caps

Bore x stroke (in): 4.00 x 3.48

Camshaft duration (@ .050 in): 212-degree intake/222-degree exhaust

Camshaft lift (in): .435 intake/.460 exhaust

Camshaft part number: 24502476

Camshaft type: hydraulic flat tapped

Compression ratio: 9.1:1

Connecting rod part number: 10108633

Connecting rods type: powdered metal steel

Crankshaft part number: 14088526

Crankshaft type: nodular iron

Cylinder head part number: 12558060

Cylinder head type: vortex iron; 64cc chambers

Displacement (cu in): 350

Engine name: Circle Track 350/350

Engine type: Chevy small block V-8

Ignition timing: 32-degree total @ 4000 rpm with vacuum advance disconnected

Maximum rpm: 5500

**NOTE:** distributor included with 350/350 engine has melanzized steel gear part number 10456413. This must be used with engines with steel camshafts or engine damage will occur.

Piston part number: 12514101

Pistons type: hypereutectic aluminum

Recommended fuel: 92 octanes

Rocker arm ratio: 1.5:1

Rocker arms part number: 10089648

Rocker arms type: stamped steel

Valve size (in): 1.94 intake/1.50 exhaust

GM crate motors may not be unsealed and may not be rebuilt without track approval before the rebuild. If permitted, the motor must be rebuilt at a track authorized motor builder. Motors that are torn down for track tech must be reassembled with all of the exact same parts at the time of tear down except those that are determined by the tech official to be damaged by the tear down process. Any tear down damaged part must be replaced with the exact same GM part.

Reassembled motor must be inspected and resealed by authorized tech center before further competition. By using a GM crate motor in competition, the race team acknowledges all responsibility for the legality of the motor upon inspection at any event regardless of any previous motor verification.

### **Transmission/Driveline and Driveline Components**

Direct drives systems of any-type will not be permitted.

The transmission must be bolted to the engine it must have forward and working reverse gear(s) and must be able to shift to forward or reverse with engine running.

All cars must be equipped with a working self-starter.

If a stock style clutch is used it must have a blow proof bell housing.

### **Driveshaft**

The driveshaft must be a minimum of 2"-inches in diameter. All drive shafts must be painted white.

Only one (1) drive shaft connected from the transmission to the center section of the rear end will be permitted.

A minimum of one (1) driveshaft hoop / sling must be fastened securely to the frame. It is recommended that two (2) driveshaft hoops / slings be used.

### **Rear End**

Any type of rear end differential / center section will be permitted.

Live-axle type rear ends will not be permitted.

Independent rear suspensions will not be permitted.

Floater-type wide-five hub assemblies will be the only hub assemblies permitted.

### **Fuel, Fuel Cells and Fuel System**

All cars must have fuel cells that meet and/or exceed FT3 specifications. The fuel cell must have a maximum capacity of 35 gallons.

The fuel cell must be enclosed completely in a container that is a minimum thickness of 20-gauge magnetic steel and/or .060"-inch aluminum.

The entire container must be visible for ease of inspection.

The fuel cell must be mounted behind the rear axle between the rear tires, a minimum of 4"-inches ahead of the rear bumper. The bottom of the fuel cell must not be any lower than the bottom of the rear end/quick change housing.

The fuel cell must be mounted with a minimum of two (2) .125"-inch thick steel straps. The straps must cover the entire cell. Fuel cells that are mounted in a square tubing frame will be permitted.

The fuel pick up must be positioned on the top or right side of the fuel cell and be constructed of steel. The fuel pick up must have a check valve.

Only racing gasoline or alcohol will be permitted for competition. Nitrous oxide, nitro-methane and/or propylene oxide will not be permitted.

Only mechanical and/or belt driven fuel pumps will be permitted. Fuel injection system(s) and/or electrical fuel pumps and/or any type of pressurized fuel system will not be permitted.

### **Exhaust - Muffler and Sound Reduction Devices**

The exhaust flow must be parallel to the ground. Exhaust systems that direct the flow toward the ground will not be permitted.

All exhaust systems/headers must end with a collector.

Mufflers are currently not required on exhaust systems. If used, no specific muffler model is mandated.

A decibel level rule may be mandated if needed and may be on short notice.

### **Traction Control Devices**

All electronic and/or computerized wheel spin and/or ignition retardation and/or acceleration limiting and/or traction control devices of any type will not be permitted.

Adjustable ping control devices, dial a chip controls, timing controls and/ or automated throttle controls will not be permitted.

Adjustable restrictor plates will not be permitted.

Remote control components of any-type will not be permitted.

Radios and/or devices for transmitting voice and/or data will not be permitted.

Data acquisition systems will not be permitted.

### **Chassis/Frame**

The wheel base minimum will be 103"-inches with a maximum wheel base of 105"-inches.

All frames must be fabricated from magnetic steel with a minimum of 2"-inches x 2"-inches or approved rectangular magnetic steel with a minimum material thickness of .083"-inches.

A minimum of 1.75" Outside Diameter magnetic steel tubing, 4130 Chrome Moly or DOM with a minimum material thickness of .083"-inches, will be permitted for frames that are fabricated from round tubing.

Rear bumpers that are stubbed may only extend a maximum of 8"-inches beyond the frame. Any stubbed rear bumper that extends further than the maximum of 8"-inches must be formed and directed 8"-inches toward the front of the car.

External rub rails will not be permitted.

All cars must be equipped with a tow hook and/or strap for the purpose of towing.

All battery supports and/or mounts must be secure and braced in two (2) horizontal positions and one (1) vertical position.

Any frame built on or after January 1st, 2006, must have the builder's unique serial number plate prominently attached to the left side roll cage upright. The plate must be welded in place. All characters on the plate must be a minimum of ½"-inch in height and the serial number must not exceed 8 characters.

### **Weight / Ballast**

Total weight of car and driver may not be less than 2,250 pounds for cars using a crate 602 GM engine and not less than 2,350 pounds if a non-crate engine is used. Maximum weight for all cars, without driver, is 2,550 pounds. No allowance given.

Weights up to 50 lbs. must be positively fastened by 2 ½-inch, minimum grade 5 bolts with a minimum of two (2) weight clamps. Threaded rods will not be permitted. All weights must be painted white and clearly labeled with the car number on it.

Any weight(s) must be securely attached to the frame below the body decking.

Any car that loses any weight/ballast during an event may be subject to a penalty.

Weights attached to the rear bumper and/or outside the frame will not be permitted.

Pellet-type and/or liquid-type weight/ballast will not be permitted.

Driver operated weight adjustment, 'weight jacking' devices will not be permitted.

Weigh-in to be after any event or qualifying. Weight to be measured as car comes off the track in the condition that it took the checkered flag. Weight measured by Selinsgrove Speedway scales. Any car that completes a time trial or finishes in the top 3 of any heat, top 5 of any main event, or otherwise as directed by speedway officials, that does not go directly to the scales first before the car stops with the crew and/or at the trailer will be disqualified and scored last for that event. Track officials may request that you shut off the engine of your car while on the scale. Driver must remain still in the seat while car is being weighed. Any car that is deemed light will be reweighed a second time. The car in question will be rolled off the scale by hand, the scales will be reset and the car immediately rolled back onto the scale by hand. Cars will not be permitted to leave the on/off ramps of the scale between reweighs unless directed by track officials. Any car required to be weighed at the completion of any event that does not meet the minimum weight requirements will be disqualified and scored behind all other cars that were scored on the same lap as the car in question. The number of cars required to be weighed for any event may be changed by track officials and teams will be notified.

**Body** - Lucas Oil Late Model rules for BODY RULES)

### **Overall Appearance**

The car must be neat in appearance and must display the car number of the front nose and the rear fuel cell. The minimum height for the number will be 6"-inches.

The car must have legible numbers on each side and on the roof a minimum of 18"-inches high,

The driver's last name must be placed in legible letters on both doors or the rocker panels.

### **General Body**

The nosepiece must match the body style of the make and manufacturer of the car and be the same as the make and manufacturer of the motor (GM, Ford, Mopar).

All cars must have a minimum half-inch (1/2") and a maximum of one (1) -inch radius at the top of fenders, doors and quarter panels. Sharp edge(s) will not be permitted.

The floor boards and firewall must completely cover the driver's area with no openings.

Fins and/or lips of any-type will not be permitted anywhere along the entire length of the car.

The body line must be a smooth even line from front to rear.

Wedge shape cars and/or body styles will not be permitted.

"Belly pans" or any type of enclosure on the bottom of the car will not be permitted. A skid plate to protect the oil pan is permitted. A maximum 1/8" skid plate will be permitted.

Wings and/or tunnels and/or any type of air deflection device will not be permitted underneath the body and/or chassis of the car.

A maximum of one (1) stone deflector, for rear mounted oil pumps, oil filters, and for the main oil tank will be permitted. The deflector may be made of steel, aluminum, or heavy gauge wire. The cover may only be mounted near the unit it is designed to protect with a maximum size of 18" x18" and only mounted from the upper right frame rail to the lower right frame rail.

Panels of any type under the rear deck running from the front to the rear of the car will not be permitted.

Any style air cleaner scoop used must be positioned in front of/or around the air cleaner and must not exceed 1"-inch in height above any part of the air cleaner. Any type of flange and/or air deflection device and/or fin that is designed to direct airflow will not be permitted.

Cockpit adjustable components with the exception of brake bias adjusters will not be permitted. Adjusters of any-type, including but not limited to adjustable shocks, hydraulic or pneumatic weight jacks, trackers, ignition boxes or similar adjustable components will not be permitted inside the cockpit of the car or within reach of the seated driver.

### **Nosepiece**

Only approved nosepieces may be used. A list of approved manufactures and part numbers for competition in Late Model competition follows: 1.) MD3 – Performance Bodies 2.) ARP 3.) Five-Star MD3 type

All nosepieces must be made of molded type material.

Two-piece noses must be positively fastened together in the center. Spacers added to gain width will not be permitted.

The nosepiece must be mounted in a manner that does not alter its original shape.

The nose shall remain flat above the nose lip/wicker bill. Alterations and/ or additions may not be made to this area other than cooling holes will be permitted.

The nosepiece can extend a maximum of fifty-two inches (52") from the center of the front hub to the farthest point extending forward.

The nosepiece must display a headlight decal package. A one-race grace period, running contrasting color tape in the shape of a headlight will be permitted.

### **Roof**

The roof length from front-to-back must be a minimum of 44"-inches with a maximum of 54" inches.

The roof width from side-to-side must be a minimum of 48"-inches to a maximum of 52"-inches.

The roof must be stock appearing and be mounted level to the body.

The minimum height of the roof will be 45"-inches with a maximum height of 48"-inches. The roof will have a maximum rake of 3"-inches.

The roof must be mounted parallel to the body and near the center of the car as viewed from the front of the car. The entire rear edge of the roof, when measured from the bottom of the roof to the top of the interior decking, shall maintain the same height measurement across the entire width of the roof.

A maximum 1-1/2" roll, turned downward will be permitted along the front of edge of the roof. A maximum 1"-inch roll, turned downward, will be permitted along the rear edge of the roof. These modifications will be permitted to improve the strength of the roof. Any other modifications to the roof will not be permitted.

Flat and/or odd shaped roofs will not be permitted. Bellied and hollowed roofs will not be permitted. 4.3.8. Any sun/antiglare shields may not exceed a 4" drop from the top roof line, and must hinge for easy exiting.

A maximum of two (2) roof edge bead rolls of a maximum height of 1/2"- inch the length of the roof will be permitted.

The roof posts and spoiler support(s) may not overlap.

Only single plated roofs will be permitted.

The maximum thickness of the roof at any point will be 1/2"-inch.

The roll cage and associated frame members above the interior panels (decking) must remain open. Enclosures will not be permitted.

### **Roof Supports and Window Side Panels**

All roof side panels must extend to the edge of the body.



The roof side panel window size must be a minimum of 10"-inches x 15"-inches and must match drawing number -4- side view. A maximum crown of two (2) inches will be permitted, measured from the center of a common tangent point on either side of the crown.

The left and right-side window panels must match.

A maximum bow of two (2")-inches outward on the window side panels as viewed from behind will be permitted.

The front roof supports up to 2"-inches in width must extend forward to the rear of the hood. Lips and/or fins will not be permitted.

### **Front Fenders, Fender Flares and Hood**

The hood and the front fenders must be level and flat from the left to the right side of the car.

The outside edges of the hood and/or the fender must remain inside the overall bodyline.

The front fender may be a maximum of 37"-inches in height, measured vertically from the ground to the top of the fender behind the front tires.

The front fender flares must be made of plastic and must not alter the original shape of the nose piece.

The front fender flares must not extend beyond the front tires more than 1"-inch per side to a maximum width, edge-to-edge, of 90"-inches in width with the wheels pointed straight.

The front fender flares can have a maximum increase in height of 2 inches.

The front fender flares must have collapsible supports.

### **Doors**

The door-to-door measurement must not exceed 76"-inches in width at the top of the doors.

The door-to-door measurement must not exceed 89"-inches overall width when measured at the bottom of the doors in the center of the car.

The doors must not exceed 37"-inches in height when measured from the ground to the top of the door.

The door sides may not break inward from the top 76"-inches and bottom 89 "-inch measurements. Hollow and/or belled doors will not be permitted.

The minimum ground clearance will be 3"-inches.

### **Quarter Panels**

The maximum distance from the center of the rear hub to the top quarter of the panel is fifty-three (53")-inches.

The quarter panels must not exceed 76"-inches in width at any point as measured at the top of the panels.

The rear deck must taper in a symmetrical manner from the center of the rear hub to the rear spoiler with a maximum width of 72"-inches.

The maximum width for the quarter panels measured from outside-to outside measured 19"-inches from the ground and/or at the bottom of the quarter panel will be 86"-inches.

Any breaks and/or bends formed in the sides of the quarter panel that move the panel toward the center of the car will not be permitted. Hollow and/or bellied panels will not be permitted.

The maximum distance from the center of the rear hub to the rear trailing edge of the quarter panel will be 48"-inches. See drawing #2 1.7A.

The maximum height from the ground to the top of the rear deck at the top of the rear quarter panel is 38"-inches.

A minimum of 2"-inches of tire clearance between the tire and the body will be required.

Skirting that extends behind the rear quarter panel will not be permitted.

### **Spoilers and Spoiler Braces/Supports**

Only aluminum and/or Lexan and/or Lexan-type rear spoilers will be permitted.

The maximum overall height of the rear spoiler will be 8"-inches. The maximum width of the rear spoiler, including braces and/or supports is 72"-inches.

The rear spoiler must begin at the deck and extend 8"-inches from that point. Suspending the spoiler to create a wing-type device will not be permitted.

The rear spoiler must begin at the rear most point of the quarter panels.

Only three spoiler braces/supports will be permitted. The front edge of the spoiler brace/support must be in line with the spoiler.

The outside spoiler supports must not be mounted any-wider than the top of the quarter panel(s) and must be centered on the rear deck.

In the event that aluminum angle is used to bracer the upper edge of the spoiler, the angle must not add to the height and/or length of the spoiler in any way.

### **Interior**

The interior of the cockpit must be a minimum of 11"-inches below the top of the roof and/or roll cage, measured perpendicular to the ground from the bottom of the roof to the cockpit deck. Roof rolls are not part of the measurement.

The side window opening(s) must be 15"-inches from the top of the door to the bottom of the roof.

Supports bars that block the right window from the driver exiting the cockpit will not be permitted.

A single rock guard (Lexan screen) tapered back from the steering wheel to the height of 1"-inch in line with the driver's chest providing the 11"-inch minimum clearance is met at any point from the roll cage to the body and/ or rock guard.

If the interior deck drops the drop must begin at the rear of the engine plate with a maximum of 4"-inches and must not drop below 4"-inches rear of the hood. The start of the dropped interior must remain closed as a part of the fire wall. The entire width must be closed off with sheet metal.

The interior must gradually taper up to the quarter panel height and must be level for a minimum of 20" inches from the rear spoiler forward.

### **Driver Compartment**

A full metal firewall fabricated from magnetic steel and/or aluminum must encompass the driver's compartment from front-to-rear, on both sides and floor boards.

All cars must be equipped with a quick-release type fully round steering wheel.

The driver compartment must have a starting switch and/or button within reach of the driver.

A clearly labeled electrical on/off 'kill' switch must be within reach of the driver is recommended.

Mirrors of any-type will not be permitted.

Radios and/or electronic and/or data communication devices will not be permitted.

Any edge and/or sheet metal end in and around the driver compartment must be protected with trim and/or beading and rounded. Sharp and protruding edges will not be permitted.

A substantial rock guard with a minimum of three (3) additional roll bars must be mounted in front of the driver. The rock guard must be made from wire screen. Windshield screens must be a minimum of .090-inches and must be securely fastened.

A fully charged fire extinguisher meeting SFI 167.1 specifications with an activation push and/or pull knob within reach of the driver is recommended

### **Suspension**

All cars must be equipped with an operating four-wheel disc brake system.

### **Shock Absorbers**

Only one rebound and one compression adjustable steel or aluminum shock is allowed. Shock bumpers are permitted. More than one shock per wheel is permitted. Driver adjustable shocks or driver adjustable weight jacks are not permitted. External canister gas shocks are permitted. No torsion bar suspension is permitted. No electronic adjusting is permitted.

Shock absorbers may not contain any "internal" spring that functions as a load bearing suspension spring, "internal" coil bump spring above or below the working piston, nor "internal" bump stop of any kind. No pneumatic springs, "air" springs or "air" shocks permitted.

Only solid material bump stops are permitted; rubber, urethane, and plastic. No coil spring or valve spring-type bump springs permitted. No convex disc bump spring permitted. The only nitrogen charged parts allowed are the shock bodies themselves and must run standard conventional springs on ALL shocks. Stack springs are permitted.

Gas or oil shocks are permitted.

### **Suspension Components/Springs**

Coil springs must be magnetic steel.

Leaf springs may be composite material or magnetic steel.

ONLY coil springs or leaf springs will be permitted. No pneumatic springs, "air" springs, or "air" shocks permitted. No more than 2 springs per shock. Must be one on top of the other.

### **Roll Cage**

All cars must have a roll cage fabricated from a minimum of 1-1/2" outside diameter with .065"-inch thick seamless magnetic steel tubing.

The side roll bars and/or door bars must extend into the door panels.

A minimum of three (3) bars must be utilized on the left side of the car in the door area.

Any of the bars that are utilized for the top portion of the roll cage, including, but not limited to the front and rear hoops, the top hoop and the uprights, must extend a minimum of 1"-inch above the driver's helmet.

All new frames and/or roll cages built on or after January 1st, 2006 an additional vertical side brace is required on the left side in vertical alignment with the steering wheel.

### **Wheels**

Only steel or aluminum wheels will be permitted for competition.

The wheels must be mounted to the hubs utilizing lug nuts. "Knock off" and/or single type wheel mounting systems will not be permitted.

The maximum wheel width that will be permitted is 14"-inches.

The maximum front track width will be 90"-inches and the maximum rear track width will be 88"-inches, measured from the outside edge of the tire to the outside edge of the tire.

Wheel spacers will be permitted provided the track width(s) do not exceed their maximum dimensions.

### **Tires**

All four tires must be:

Hoosier: 1300 or harder

American Racer: 44 or harder

Minimum durometer reading of 32 at anytime

All crate engine cars will have an open tire rule

The maximum size for any tire in competition is 11"-inches x 29"-inches x 15"-inches, unless otherwise specified in written form to all competitors.

The maximum outside circumference of the tire will be 93"-inches, unless otherwise specified in written form to all competitors.

The maximum width of the tires measured from the outside edge(s) of the sidewalls across the face of the tire will be 16  $\frac{3}{4}$ "-inches. There will be a tire hoop used for inspection and the tire must pass through the tire hoop freely, without any manipulation or outside contact.

The tire rule for any event may be amended in written form, to all competitors per any technical bulletin.

The altering of any tire compound, by any means will not be permitted. Chemical alteration of the tread carcass and/or tread compound, such as tire 'soaking' and/or the introduction of tread 'softener' and/or physical defacement (removal, altering and/or covering) of tire sidewall markings in any manner will not be permitted. If any competitor is found to have altered their tires any penalty deemed appropriate by Late Model Officials may be issued. Any tire may be inspected and/or analyzed for alteration at any time. This will consist of a process as determined by the independent laboratory that performs the analysis. A "Chain of Custody" process will be outlined with the competitor upon inspection of the tires. The analysis process will require shipment of the tire to the selected laboratory.. If a penalty is issued, the event the tire was used in will be penalized.

Monies won in an event may be held until the final determination is made by the independent laboratory.

Chemical alterations, vulcanizing, tire softening, defacing and/or altering the face of the tire lettering and/or tire stamping will not be permitted.

Chemicals or tire softening is not permitted at any time. Tires may be inspected at any time. Any violation with any tire presented for competition may result in immediate disqualification from the events and/or other penalties including but not limited to; loss of money, fine, loss of points and/or suspension.

Only approved tires will be permitted for use in competition.

### **Radios/Transponders:**

No radios (one way or two way) or other means of electronic communications between the driver and anyone other than track officials is permitted.

All drivers are required to use a receiver capable of receiving frequency 454.000 for one-way communications from track officials.

Limited Late Models are required to use transponders. Rental units are available from the speedway.

Transponders for Limited Late Models should be mounted on the rear of the car near the oil tank.

Transponders must be mounted in a vertical position pointing straight down and as close to the ground as possible. There cannot be any metal, carbon fiber or other material that would deflect or block the signal between the transponder and the ground.

Other than wiring used to connect direct powered units the transponder should not be mounted within 12" of any device that generates, transports or stores electric or magnetic energy (individual race cars may require a greater distance or shielding).

Transponders/brackets should be riveted, wire tied or clamped to the mounting point with additional wire ties, clamps or other securing devices encompassing the entire mounting point /bracket / transponder for additional security.

Speedway is not responsible for lost/damaged transponders. Damaged/Lost units rented from Speedway are the responsibility of renter.

It is each race teams responsibility to assure that the transponder they are using is mounted properly and in working condition at all times car is on track.

Changes in mounting location may only be approved by speedway electronic scoring technicians and only in the case of transponders not reading correctly. This shall only be approved if it is determined by speedway electronic scoring technicians that all other possibilities and scenarios to correct the situation have been exhausted.

### **Personal Safety Equipment:**

#### **General**

Each competitor is solely responsible of for the effectiveness and proper installation, per the manufacturer's specifications, of personal safety equipment and determining it to be adequate for competition at every event. Each competitor is expected to investigate and educate themselves for continuing improvement regarding their own personal safety equipment.

#### **Seat Belt/Restraint System**

Each car will be equipped with minimum of an SFI 16.5 or SFI 16.1 approved restraint system, until the date of the belt expiration (two years from the date of manufacturer). Seat belt restraint systems shall be installed and used in accordance with manufacturer's instructions. *In any type of manufacturer's installation the fasteners should be magnetic steel unless using type of mount in which the seat belt wraps around the roll cage.*

Seat belt material should not be permitted to come in contact with any sharp or metal edge, including when the material passes through the seat.

#### **Protective Clothing**

All drivers will be required to wear a fire resistant driving uniform meeting minimum of the SFI 3.2A/5 specification and display a valid SFI 3.2A/5 label.

All drivers should wear fire resistant accessories including but not limited to; head sock, under garments, shoes, and socks.

All drivers are required to wear fire resistant gloves. Shoes and gloves will be required to meet minimum of the SFI 3.3 specifications and display a valid SFI 3.3 label.

#### **Seats**

Aluminum and/or carbon fiber-type seats will be permitted. It is recommended that aluminum seats have an FIA and/or SFI rating, any carbon-fiber-type, composite seats must meet the SFI Rating 39.2. All seats must be mounted to the frame as required by the seat and chassis manufacturer.

All areas surrounding the head should have padding.

A right side head restraint net and/or support are required. All head restraint nets should be equipped with quick release mechanisms.

### **Helmets**

All drivers will be required to wear a full-face helmet with a minimum safety rating of FIA 8860-2004, FIA 8860-2010, Snell SA 2005, Snell SA 2010, Snell SAH 2010 and/or a valid SFI 31.1/2005 label.

It is strongly recommended that helmets should be fitted with the Eject™ helmet removal system.

Head and Neck restraints are strongly recommended. The head and neck restraint system must be mounted and connected to the helmet per the helmet manufacturer and head and neck manufacturer instructions.

Arm restraints are recommended and must be connected and used as instructed by the manufacturer.

### **Other**

Cars will not be permitted to make a qualifying attempt without passing technical inspection. All cars must be available for inspection prior to the time of the driver's meeting. Following the driver's meeting, covers of any-type on the racecar will not be permitted.

All cars may be subject to technical inspection at any time.

Full or partial car covers will be permitted only when there is inclement weather and/or the car is in its designated pit stall. All covers shall be removed prior to the car leaving its designated pit stall.

SFI-approved and labeled seat, roll bar, knee and steering pads and/or padding is recommended.

It is recommended that all teams have a fire extinguisher in the rear of their transporter. The fire extinguisher is recommended to be a minimum Of 2.5 gallons FFF type chemical and/or equivalent.

All car must have window net to race.

**\*Note - these rules are subject to change during the racing season. \***

**The officials' interpretation of these rules is FINAL.**

**Variations from any specification or rule must be approved by the speedway tech officials.**

**All cars are subject to technical inspection at any time. Refusal to allow technical inspection may result in disqualification and loss of points and prize money for that event.**

### **PROTESTING SPECIFIC COMPONENTS ON ANY RACE CAR:**

Only a driver from that particular race may protest a component on another competitor's car. Any specific engine, rear end, suspension components, etc., of any driver's car may be protested by any driver in that feature after the race for **the amount designated** in terms of cash. All parties concerned shall be bound by decisions rendered by speedway management or tech officials. All measurements will be with Selinsgrove Speedway equipment or authorized agents.

**PROTESTED ITEM:** The protester may only protest **ONE** specific component

**TIME OF THE PROTEST:** The protester's written protest clearly state the name of the driver making the protest, the name of the driver being protested and the component they are protesting. The protest must also be signed and dated. The written protest **MUST** be accompanied by a full payment of **\$500.00** in cash and must be presented to the division's tech inspector **NO** later than **fifteen (15) minutes** following the finish of the race. A driver may protest only the driver finishing directly in the position in front of him and on the lead lap. Once a protest is made, it may not be withdrawn. All purse and points are to be distributed after a decision on the protest has been made. Technical inspectors will not accept verbal protests or protests which are not accompanied by the required protest fee.

**CHECKING THE PROTEST:** After the technical inspector has completed his/her normal post race inspection(s) then and only then will the protest process begin.

Along with tech officials the only persons permitted in the tech area are the driver and one crewmember from the car going through the protest tech process. Tech officials may permit a second crewmember to assist if they deem it necessary.

**THE PROTESTER'S CAR WILL BE CHECKED FIRST FOR THE LEGALITY OF THE SAME COMPONENT FOR WHICH THEY FILED THEIR PROTEST.**

**WHEN THE PROTESTER'S CAR IS FOUND TO HAVE AN ILLEGAL COMPONENT:** After inspection, if the protester's car is found to have an illegal component, the driver of that car will be disqualified from that event, forfeits all prizes and honors earned at the event and face the possibility of more penalties at the discretion of Speedway Management. The illegal parts will also be confiscated by speedway management immediately. The protest money will be forfeited and kept by speedway management for distribution as they see fit.

If a decision at the track cannot be made, then the component will be kept for further testing and validating at the discretion of speedway management until a final decision on legality can be determined. The protested component may be sent to an independent tester at the protester's expense for review.

It is the driver's duty to prove his legality, not the tech official's duty to prove the violation. Only the protested component may result in a disqualification during the protest process – no other components will be considered regardless of their legality.

If the component in question on the protester's car is found to be illegal the car being protested **WILL NOT** be checked.

**WHEN THE PROTESTER'S CAR IS FOUND TO HAVE A LEGAL COMPONENT:** After inspection, if the protester's car is found to have a legal component, the car being protested will be checked.

**REFUSAL OF A PROTEST:** If the driver of the protesting car does not allow inspection under these terms, he or she will be disqualified, forfeit the protest fee to speedway management, forfeit all points, purse monies, prizes and awards earned at that event and possibly suffer more penalties as determined by Speedway Management. The car being protested will then **NOT** be checked.

**WHEN THE PROTESTED CAR IS FOUND TO HAVE AN ILLEGAL COMPONENT:** After inspection, if the protested component is found illegal, the driver of that car will be disqualified from that event, forfeits all prizes and honors earned at the event and face the possibility of more penalties at the discretion of Speedway Management. The illegal parts will also be confiscated by speedway management immediately. The protest money will be returned to the team filing the



protest.

If a decision at the track cannot be made, then the component will be kept for further testing and validating at the discretion of speedway management until a final decision on legality can be determined. The protested component may be sent to an independent tester at the protester's expense for review.

It is the driver's duty to prove his legality, not the tech official's duty to prove the violation. Only the protested component may result in a disqualification during the protest process – no other components will be considered regardless of their legality.

**WHEN THE PROTESTED CAR IS FOUND TO HAVE A LEGAL COMPONENT:** After inspection, if the protested component is found legal, the protest money will be given to the driver of the car from which the component was protested (less a **\$100.00** inspection fee and shipping charges (if any as determined by Speedway Management)).

**REFUSAL OF A PROTEST:** If the driver of the protested car does not allow inspection under these terms, he or she will be disqualified, forfeit all points, purse monies, prizes and awards earned at that event and possibly suffer more penalties as determined by Speedway Management.

**SCORING PROTESTS:** Only the driver or car owner may protest to the scorers and only after all racing is completed for the evening. Scoring protests may be verbal and do not require a protest fee.